

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Ammonia Mixture, Flammable, Corrosive	Trade Name: Ammonia Mixture, Flammable, Corrosive
Product Use: Not available.	
Chemical Name: Ammonia Mixture, Flammable, Corrosive	Synonym: Not applicable.
Chemical Formula: Not applicable.	Chemical Family: Not applicable.
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2 Phone: 905-803-1600 Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Ammonia	1 - 99.999	7664-41-7	Not available.	2000 ppm	25 ppm
AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES:					
Butane	0 - 99	106-97-8	Not available.	Not available.	1000 ppm
1-Butene	0 - 99	106-98-9	Not available.	Not available.	250 ppm
Deuterium	0 - 99	7782-39-0	Not available.	Not available.	Not available.
Ethane	0 - 99	74-84-0	Not available.	Not available.	1000 ppm.
Ethylene	0 - 99	74-85-1	Not available.	Not available.	200 ppm
Hydrogen	0 - 99	1333-74-0	Not available.	Not available.	Simple asphyxiant.
Isobutane	0 - 99	75-28-5	Not available.	Not available.	1000 ppm
Methane	0 - 99	74-82-8	Not available.	Not available.	1000 ppm
Propane	0 - 99	74-98-6	Not available.	Not available.	1000 ppm
Propylene	0 - 99	115-07-1	Not available.	Not available.	500 ppm

3. Hazards Identification



Emergency Overview



DANGER! Toxic, flammable, corrosive, high-pressure gas. Harmful or fatal if inhaled. Can form explosive mixture with air. Causes eye, skin, and respiratory tract burns. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE:

Absorbed through skin. Eye contact. Inhalation. Ingestion.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION: Overexposure to concentrations moderately above the threshold Limit Value (TLV) of 25 ppm for ammonia may cause irritation of the eyes, nose, and throat. Higher concentrations may cause breathing difficulty, chest pain, bronchospasm, pink frothy sputum, and pulmonary edema. Overexposure may predispose to the development of acute bronchitis and pneumonia.

SKIN CONTACT: Exposure to gas at high concentrations may cause chemical burns.

SKIN ABSORPTION: Prolonged or widespread skin contact with the liquid may result in the absorption of harmful amounts of material.

SWALLOWING: An unlikely route of exposure. This product is a gas at normal temperature and pressure, but may cause chemical burns of the mouth, throat, esophagus and stomach.

EYE CONTACT: Exposure to gas may cause pain and excessive tearing, with acute corneal injury at high concentrations.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

Chronic exposure may cause chemical pneumonitis and kidney damage.

OTHER EFFECTS OF OVEREXPOSURE:

None currently known.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Inhalation may aggravate asthma and inflammatory or fibrotic pulmonary disease. The skin irritating properties of the material may aggravate.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

None currently known.

CARCINOGENICITY:

Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Ethylene].
Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Propylene].

4. First Aid Measures

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

SKIN CONTACT:

Immediately flush affected areas with water for at least 15 minutes while removing contaminated clothing and shoes. Discard clothing and shoes. Call a physician.

SWALLOWING:

This product is a gas at normal temperature and pressure. Rinse mouth with water. Give at least two glasses of water or milk at once. Do not induce vomiting. Call a physician.

EYE CONTACT:

Immediately flush eyes with running water for at least 15 minutes. The eyelids must be held open and away from the eyeball to ensure that all surfaces are flushed thoroughly. See a physician, preferably an ophthalmologist, immediately.

NOTES TO PHYSICIAN:

Victims of overexposure should be observed for at least 72 hours for delayed onset of pulmonary edema.

The hazards of this material are mainly due to its severe irritant and corrosive properties on the skin and mucosal surfaces. There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.

5. Fire Fighting Measures

FLAMMABLE : Yes.	IF YES, UNDER WHAT CONDITIONS?	Forms explosive mixtures with air and oxidizing agents.
FLASH POINT (test method) Flammable Gas.	AUTOIGNITION TEMPERATURE	Not available..
FLAMMABLE LIMITS IN AIR, % by volume:	LOWER: Not available.	UPPER: Not available.

EXTINGUISHING MEDIA:

CO2, dry chemical, water spray or fog.

SPECIAL FIRE FIGHTING PROCEDURES:

DANGER! Evacuate all personnel from danger area. Do not approach area without self-contained breathing apparatus and protective clothing. Immediately cool containers with water spray from maximum distance, taking care not to extinguish the flames. Reduce corrosive vapours with water spray or fog. Stop flow of gas if without risk while continuing cooling water spray. Remove all containers from area of fire if without risk. Allow fire to burn out.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Flammable, toxic, corrosive gas. Container may rupture due to heat of fire. Do not extinguish flames due to possibility of explosive re-ignition. Corrosive vapours may spread from spill. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with approved device. No part of a container should be subjected to temperature higher than 52 C.

HAZARDOUS COMBUSTION PRODUCTS:

Nitrogen and water

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not available.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

DANGER! **Toxic, flammable, corrosive, high-pressure gas.** May form explosive mixtures with air. Immediately evacuate all personnel from danger area. Reverse flow into cylinder may cause rupture. Use self-contained breathing apparatus and protective clothing where needed. Remove all sources of ignition if without risk. Reduce vapors with fog or fine water spray. Shut off leak if without risk. Ventilate area or move cylinder to a well-ventilated area. Flammable vapors may spread from spill. Before entering area, especially confined areas, check atmosphere with an appropriate device.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Electrical equipment must be non-sparking or explosion-proof. Leak check system with soapy water; never use a flame. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

Toxic, flammable high-pressure gas. May be fatal if inhaled. Do not breathe gas. Use piping and equipment adequately designed to withstand pressures to be encountered. **May form explosive mixtures with air.** Keep away from heat, open flame and sparks. Ground all equipment. Use only spark-proof tools and explosion-proof equipment. Store and use with adequate ventilation at all times. Use only in a closed system. Close valve after each use; keep closed even when empty. **When returning cylinder to supplier, be sure valve is closed, then install valve outlet plug tightly. Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, provincial, and local laws, then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Explosion-proof, corrosion resistance system is acceptable.

MECHANICAL (general): Inadequate.
See SPECIAL.

SPECIAL: Use only in a closed system. Explosion-proof, corrosion resistant, forced draft fume hood is preferred.

OTHER: See SPECIAL.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Select in accordance with provincial regulations, local bylaws or guidelines. Selection should also be based on the current CSA standard Z94.4, "Selection, Care and Use of Respirators". Respirators should also be approved by NIOSH and MSHA.

SKIN PROTECTION: Neoprene gloves.

EYE PROTECTION: Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

PHYSICAL STATE: Gas.	FREEZING POINT: Not available.	pH: Not available.
BOILING POINT: Not available.	VAPOUR PRESSURE: Not applicable.	MOLECULAR WEIGHT: Not applicable.
SPECIFIC GRAVITY: Not available. LIQUID (Water = 1)	SOLUBILITY IN WATER: Not available.	
SPECIFIC GRAVITY: Not available. VAPOUR (air = 1)	EVAPORATION RATE (Butyl Acetate=1): Not available.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable.
VAPOUR DENSITY: Not available.	% VOLATILES BY VOLUME: Not available.	ODOUR THRESHOLD: Not available.

APPEARANCE & ODOUR: Colourless gas at normal temperature and pressure. Pungent, irritating odour.

10. Stability and Reactivity

STABILITY:	The product is stable.
CONDITIONS OF CHEMICAL INSTABILITY:	See Section 7.
INCOMPATIBILITY (materials to avoid):	Gold, silver, mercury, oxidizing agents, halogens, halogenated compounds, acids, copper, copper-zinc alloys (brass), aluminum, chlorates, zinc.
HAZARDOUS DECOMPOSITION PRODUCTS:	Hydrogen may be formed at temperatures in excess of 840 C in the absence of air and oxygen. The normal products of combustion and nitrogen and water.
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS OF REACTIVITY:	None.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

TDG/IMO SHIPPING NAME: Compressed gas, toxic, flammable, n.o.s. (ammonia).

HAZARD CLASS:	IDENTIFICATION #:	PRODUCT REPORTABLE QUANTITY (PRO):
CLASS 2.3 (2.1) Toxic and flammable gas.	UN1953	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more.

SHIPPING LABEL(s): Toxic gas, Flammable gas (subsidiary)

PLACARD (when required): Toxic gas

SPECIAL SHIPPING INFORMATION:LL

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list

WHMIS (Canada) Class A: Compressed gas.
Class B-1: Flammable gas.
Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).
Class E: Corrosive gas.

International Regulations

EINECS Not available.

DSCL (EEC) R20- Harmful by inhalation.

International Lists No products were found.

Product Name: Ammonia Mixture,
Flammable, Corrosive

MSDS# E-6746-I

Date: Oct 15, 2016

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMIS RATINGS:

HEALTH 2

FLAMMABILITY 4

PHYSICAL HAZARD 2

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED:	CGA-705
PIN-INDEXED YOKE:	Not available.
ULTRA-HIGH-INTEGRITY CONNECTION:	Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

- AV-1 Safe Handling and Storage of Compressed Gas
- P-1 Safe Handling of Compressed Gases in Containers
- P-14 Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmospheres
- SB-2 Oxygen-Deficient Atmospheres
- V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
- V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
- Handbook of Compressed Gases, Fifth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

PREPARATION INFORMATION:

DATE: October 15, 2016
DEPARTMENT: Safety and Environmental Services
TELEPHONE: 905-803-1600

Product Name: Ammonia Mixture,
Flammable, Corrosive

MSDS# E-6746-H

Date: Oct 15, 2016

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Praxair and the *Flowing Airstream* design are trademarks of
Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2

Copyright © 2016, Praxair Canada Inc.

Page 8 of 8