

SECTION 1: Identification**1.1. Product identifier**

Product form : Mixture
Product name : P-18-28547
Other means of identification : HY- BD 1-5%, AC 1ppm-9999%, CO 1ppm-0.0999%, ET, 1-30%, EY 1-40%, ME 1-10%, PR 1ppm-1%, PY 1ppm-1%
Product group : Specialty Mixtures

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Praxair Canada inc.
1200 – 1 City Centre Drive
Mississauga - Canada L5B 1M2
T 1-905-803-1600 - F 1-905-803-1682
www.praxair.ca

1.4. Emergency telephone number

Emergency number : 1-800-363-0042
Call emergency number 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product.
For routine information, contact your supplier or Praxair sales representative.

SECTION 2: Hazard identification**2.1. Classification of the substance or mixture****GHS-CA classification**

Flam. Gas 1 H220
Liquefied gas H280
Muta. 1 H340
Carc. 1 H350

2.2. GHS Label elements, including precautionary statements**GHS-CA labelling**

Hazard pictograms :   

Signal word : DANGER

Hazard statements : **EXTREMELY FLAMMABLE GAS**
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
MAY CAUSE GENETIC DEFECTS
MAY CAUSE CANCER
MAY FORM EXPLOSIVE MIXTURES WITH AIR.
BURNS WITH INVISIBLE FLAME.

Precautionary statements : Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing gas, vapours
Do not get in eyes, on skin, or on clothing.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Use and store only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye protection, respiratory protection, and/or face protection.
IF exposed or concerned: Get medical advice/attention
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
In case of leakage, eliminate all ignition sources
Store locked up
Dispose of contents/container in accordance with container Supplier/owner instructions.
Protect from sunlight when ambient temperature exceeds 52°C (125°F).
Use a back flow preventive device in the piping.
Close valve after each use and when empty.
Do not open valve until connected to equipment prepared for use.
Open valve slowly.

2.3. Other hazards

Other hazards not contributing to the classification : Asphyxiant in high concentrations.

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	CAS No.	% (Vol)	Common Name (synonyms)
Hydrogen	(CAS No) 1333-74-0	1 - 96.9996	Hydrogen, compressed / Hydrogen molecule H ₂ / Hydrogen
Ethylene	(CAS No) 74-85-1	1 - 40	Ethene / Ethylene, compressed / Ethylene, refrigerated liquid
Ethane	(CAS No) 74-84-0	1 - 30	Ethyl hydride / ETHANE
Methane	(CAS No) 74-82-8	1 - 30	Marsh gas / Natural gas, refrigerated liquid / Methane, compressed
Propane	(CAS No) 74-98-6	0.0001 - 30	Propane liquefied / Normal propane / n-Propane / PROPANE
1,3-Butadiene	(CAS No) 106-99-0	1 - 5	Butadiene / Butadiene, 1,3- / Buta-1,3-diene / Divinyl / Biethylene
Acetylene	(CAS No) 74-86-2	0.0001 - 3	
Propylene	(CAS No) 115-07-1	0.0001 - 1	Propylene / 1-Propene / n-Propene / 1-Propylene / Prop-1-ene
Carbon monoxide	(CAS No) 630-08-0	0.00000001 - 0.00000999	Carbon monoxide, compressed / Compressed carbon monoxide / Carbon oxide (CO) / Carbon(II) oxide / Carbon oxide

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately..

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : None.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Carbon dioxide, Dry chemical, Water spray or fog. Use extinguishing media appropriate for surrounding fire.

5.2. Unsuitable extinguishing media

No additional information available

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

5.3. Specific hazards arising from the hazardous product

- Fire hazard : **EXTREMELY FLAMMABLE GAS.**
- Explosion hazard : **EXTREMELY FLAMMABLE GAS.** Forms explosive mixtures with air and oxidizing agents.
- Reactivity : No reactivity hazard other than the effects described in sub-sections below.
- Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

5.4. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with their provincial and local fire code regulations.
- Protection during firefighting : Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen. **DANGER! FLAMMABLE, HIGH PRESSURE GAS..**
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized.)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.

6.2. Methods and materials for containment and cleaning up

6.3. Reference to other sections

For further information refer to section 8: Exposure controls/personal protection

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g, NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,3-Butadiene (106-99-0)		
USA - ACGIH	ACGIH TLV-TWA (ppm)	2 ppm
USA - OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA - OSHA	OSHA PEL (STEL) (ppm)	5 ppm (see 29 CFR 1910.1051)
Canada (Quebec)	VEMP (mg/m ³)	4.4 mg/m ³
Canada (Quebec)	VEMP (ppm)	2 ppm
Alberta	OEL TWA (mg/m ³)	4.4 mg/m ³
Alberta	OEL TWA (ppm)	2 ppm
British Columbia	OEL TWA (ppm)	2 ppm
Manitoba	OEL TWA (ppm)	2 ppm
New Brunswick	OEL TWA (mg/m ³)	4.4 mg/m ³
New Brunswick	OEL TWA (ppm)	2 ppm
New Foundland & Labrador	OEL TWA (ppm)	2 ppm
Nova Scotia	OEL TWA (ppm)	2 ppm
Nunavut	OEL STEL (ppm)	4 ppm
Nunavut	OEL TWA (ppm)	2 ppm
Northwest Territories	OEL STEL (ppm)	4 ppm
Northwest Territories	OEL TWA (ppm)	2 ppm
Ontario	OEL TWA (ppm)	2 ppm
Prince Edward Island	OEL TWA (ppm)	2 ppm
Québec	VEMP (mg/m ³)	4.4 mg/m ³
Québec	VEMP (ppm)	2 ppm
Saskatchewan	OEL STEL (ppm)	4 ppm
Saskatchewan	OEL TWA (ppm)	2 ppm
Yukon	OEL STEL (mg/m ³)	2750 mg/m ³

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

1,3-Butadiene (106-99-0)		
Yukon	OEL STEL (ppm)	1250 ppm
Yukon	OEL TWA (mg/m ³)	2200 mg/m ³
Yukon	OEL TWA (ppm)	1000 ppm
Carbon monoxide (630-08-0)		
USA - ACGIH	ACGIH TLV-TWA (ppm)	25 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	55 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Canada (Quebec)	VECD (mg/m ³)	230 mg/m ³
Canada (Quebec)	VECD (ppm)	200 ppm
Canada (Quebec)	VEMP (mg/m ³)	40 mg/m ³
Canada (Quebec)	VEMP (ppm)	35 ppm
Alberta	OEL TWA (mg/m ³)	29 mg/m ³
Alberta	OEL TWA (ppm)	25 ppm
British Columbia	OEL STEL (ppm)	100 ppm
British Columbia	OEL TWA (ppm)	25 ppm
Manitoba	OEL TWA (ppm)	25 ppm
New Brunswick	OEL TWA (mg/m ³)	29 mg/m ³
New Brunswick	OEL TWA (ppm)	25 ppm
New Foundland & Labrador	OEL TWA (ppm)	25 ppm
Nova Scotia	OEL TWA (ppm)	25 ppm
Nunavut	OEL STEL (mg/m ³)	460 mg/m ³
Nunavut	OEL STEL (ppm)	190 ppm
Nunavut	OEL TWA (mg/m ³)	57 mg/m ³
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (ppm)	190 ppm
Northwest Territories	OEL TWA (ppm)	25 ppm
Ontario	OEL TWA (ppm)	25 ppm
Prince Edward Island	OEL TWA (ppm)	25 ppm
Québec	VECD (mg/m ³)	230 mg/m ³
Québec	VECD (ppm)	200 ppm
Québec	VEMP (mg/m ³)	40 mg/m ³
Québec	VEMP (ppm)	35 ppm
Saskatchewan	OEL STEL (ppm)	190 ppm
Saskatchewan	OEL TWA (ppm)	25 ppm
Yukon	OEL STEL (mg/m ³)	440 mg/m ³
Yukon	OEL STEL (ppm)	400 ppm
Yukon	OEL TWA (mg/m ³)	55 mg/m ³
Yukon	OEL TWA (ppm)	50 ppm
Ethane (74-84-0)		
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL TWA (ppm)	1000 ppm
Nunavut	OEL STEL (ppm)	1250 ppm
Nunavut	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Ethane (74-84-0)		
Saskatchewan	OEL TWA (ppm)	1000 ppm
Ethylene (74-85-1)		
USA - ACGIH	ACGIH TLV-TWA (ppm)	200 ppm
USA - ACGIH	Remark (ACGIH)	Asphyxia
Alberta	OEL TWA (mg/m ³)	229 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Methane (74-82-8)		
British Columbia	OEL TWA (ppm)	1000 ppm
Nunavut	OEL STEL (ppm)	1250 ppm
Nunavut	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Propane (74-98-6)		
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Canada (Quebec)	VEMP (mg/m ³)	1800 mg/m ³
Canada (Quebec)	VEMP (ppm)	1000 ppm
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1800 mg/m ³
Québec	VEMP (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Propylene (115-07-1)		
USA - ACGIH	ACGIH TLV-TWA (ppm)	500 ppm
Alberta	OEL TWA (mg/m ³)	860 mg/m ³
Alberta	OEL TWA (ppm)	500 ppm
British Columbia	OEL TWA (ppm)	500 ppm

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

Propylene (115-07-1)		
Manitoba	OEL TWA (ppm)	500 ppm
New Foundland & Labrador	OEL TWA (ppm)	500 ppm
Nova Scotia	OEL TWA (ppm)	500 ppm
Ontario	OEL TWA (ppm)	500 ppm
Prince Edward Island	OEL TWA (ppm)	500 ppm

Hydrogen (1333-74-0)		
USA - ACGIH	Remark (ACGIH)	Simple asphyxiant

8.2. Appropriate engineering controls

Appropriate engineering controls : Use an explosion-proof local exhaust system. Local exhaust and general ventilation must be adequate to meet exposure standards. MECHANICAL (GENERAL): **Inadequate - Use only in a closed system.** Use explosion proof equipment and lighting. Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment : Gloves. Face shield. Safety glasses.



Hand protection : Wear work gloves when handling containers. Wear heavy rubber gloves where contact with product may occur.

Eye protection : Wear safety glasses with side shields. Safety eye wear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

Respiratory protection : **Respiratory protection:** Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below TLV. Select in accordance with provincial regulations, local bylaws or guidelines. Selection should be based on the current CSA standard Z94.4, "Selection, Care, and Use of Respirators." Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Thermal hazard protection : Wear cold insulating gloves when transfilling or breaking transfer connections.

Other information : **Other protection :** Safety shoes for general handling at customer sites. Metatarsal shoes and cuffless trousers for cylinder handling at packaging and filling plants. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines. For working with flammable and oxidizing materials, consider the use of flame resistant anti-static safety clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: No data available
Colour	: Colourless.
Odour	: No data available.
Odour threshold	: No data available
pH	: Not applicable.
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Vapour pressure	: Not applicable.
Vapour pressure at 50 °C	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: Water: No data available
Log Pow	: Not applicable.
Log Kow	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Viscosity, kinematic (calculated value) (40 °C)	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: None.
Flammability (solid, gas)	: Flammable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	: Stable under normal conditions.
Conditions to avoid	: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1,3-Butadiene (106-99-0)

LC50 inhalation rat (ppm)	220000 ppm/1h
---------------------------	---------------

Carbon monoxide (630-08-0)

LC50 inhalation rat (ppm)	3760 ppm/1h
---------------------------	-------------

Hydrogen (1333-74-0)

LC50 inhalation rat (ppm)	> 15000 ppm/1h
---------------------------	----------------

Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: MAY CAUSE GENETIC DEFECTS.
Carcinogenicity	: MAY CAUSE CANCER.
Reproductive toxicity	: Not classified

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

P-18-28547	
Persistence and degradability	No ecological damage caused by this product.
1,3-Butadiene (106-99-0)	
Persistence and degradability	Not readily biodegradable.
Ethane (74-84-0)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Ethylene (74-85-1)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Methane (74-82-8)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Propane (74-98-6)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Propylene (115-07-1)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Hydrogen (1333-74-0)	
Persistence and degradability	No ecological damage caused by this product.

12.3. Bioaccumulative potential

P-18-28547	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
1,3-Butadiene (106-99-0)	
BCF fish 1	13 - 19.1
Log Pow	1.99
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Carbon monoxide (630-08-0)	
Log Kow	Not applicable.
Ethane (74-84-0)	
Log Pow	1.81
Log Kow	Not applicable.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Ethylene (74-85-1)	
BCF fish 1	4 - 4.6
Log Pow	1.13
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Methane (74-82-8)	
Log Pow	1.09
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Propane (74-98-6)	
Log Pow	2.36
Log Kow	Not applicable.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Propylene (115-07-1)	
Log Pow	1.77
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Hydrogen (1333-74-0)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

P-18-28547	
Mobility in soil	No data available.
Log Pow	Not applicable.
Log Kow	Not applicable.
1,3-Butadiene (106-99-0)	
Log Pow	1.99
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Carbon monoxide (630-08-0)	
Mobility in soil	No data available.
Log Kow	Not applicable.
Ethane (74-84-0)	
Mobility in soil	No data available.
Log Pow	1.81
Log Kow	Not applicable.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Ethylene (74-85-1)	
Log Pow	1.13
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Methane (74-82-8)	
Log Pow	1.09
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Propane (74-98-6)	
Mobility in soil	No data available.
Log Pow	2.36
Log Kow	Not applicable.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Propylene (115-07-1)	
Log Pow	1.77
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Hydrogen (1333-74-0)	
Mobility in soil	No data available.
Log Pow	Not applicable.
Log Kow	Not applicable.
Ecology - soil	No ecological damage caused by this product.

12.5. Other adverse effects

Effect on the ozone layer : None.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

TDG

UN-No. (TDG) : UN3161
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.

ERAP Index : 3 000
Explosive Limit and Limited Quantity Index : 0.125 L

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 3161
Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG) : 2.1 - Flammable gases

IATA

UN-No. (IATA) : 3161
Proper Shipping Name (IATA) : LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. National regulations

1,3-Butadiene (106-99-0)

Listed on the Canadian DSL (Domestic Substances List)

Acetylene (74-86-2)

Listed on the Canadian DSL (Domestic Substances List)

Carbon monoxide (630-08-0)

Listed on the Canadian DSL (Domestic Substances List)

Ethane (74-84-0)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene (74-85-1)

Listed on the Canadian DSL (Domestic Substances List)

Methane (74-82-8)

Listed on the Canadian DSL (Domestic Substances List)

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

Propylene (115-07-1)

Listed on the Canadian DSL (Domestic Substances List)

Hydrogen (1333-74-0)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

1,3-Butadiene (106-99-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Acetylene (74-86-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Carbon monoxide (630-08-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Ethane (74-84-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Ethylene (74-85-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Methane (74-82-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Propane (74-98-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Propylene (115-07-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Hydrogen (1333-74-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Date of issue : 16/08/2017

Revision date : 25/08/2017

Indication of changes:

Training advice : Ensure operators understand the flammability hazard.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



P-18-28547

Safety Data Sheet P-18-28547

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 08-16-2017

Revision date: 08-25-2017

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair Canada Inc, it is the user's obligation to determine the conditions of safe use of the product. Praxair Canada Inc, SDSs are furnished on sale or delivery by Praxair Canada Inc, or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.ca. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write Praxair Canada Inc, (Phone: 1-888-257-5149; Address: Praxair Canada Inc, 1 City Centre Drive, Suite 1200, Mississauga, Ontario, L5B 1M2).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

SDS Canada (GHS) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.